


## Notes:

 Orientation marks are provided to assist in robot teaching.
 SM on Master part number indicates PNP Lock/Unlock sensors. Lock/Unlock sensing is optional.


3. Ready to Lock sensor is available.

4. Plates available for several boss sizes.\


5. QC max static moment rating Mxy=2710Nm, assuming all 10SHCS are used. QC Moment rating Mxy=1355Nm, if 6 fasteners are used on master.




## QC-160 Euro Master Assembly



## QC-160 Euro Tool Assembly





NOTES: UNLESS OTHERWISE SPECIFIED.

DO NOT SCALE DRAWING. ALL DIMENSIONS ARE IN MILLIMETERS.



DRAWN BY: S. Jeffers, 6/20/2017

1031 Goodworth Drive, Apex, NC 27539, USA Tel: +1.919.772.0115 Email: info@ati-ia.com Fax: +1.919.772.8259 www.ati-ia.com ISO 9001 Registered Company

PROPERTY OF ATI INDUSTRIAL AUTOMATION, INC. NOT TO BE REPRODUCED IN ANY MANNER EXCEPT ON ORDER OR WITH PRIOR WRITTEN AUTHORIZATION OF ATI.



3rd ANGLE PROJECTION

CHECKED BY: M. Gala, 6/21/2017

PROJECT # SHEET 3 OF 3 QC-160 Tool Changer, Euro

DRAWING NUMBER 1:2 9630-20-160-E REVISION

02