







TABLE 1: BINARY OUTPUT OF TOOL ID

Switch	Pin	Pin	Pin	Pin	
Selection	Р	S	R	Т	Switch
0	0	0	0	0	
1	0	0	0	1	
2	0	0	1	0	
3	0	0	1	1	
4	0	1	0	0	
5	0	1	0	1	
6	0	1	1	0	
7	0	1	1	1	
8	1	0	0	0	
9	1	0	0	1	
Α	1	0	1	0	
В	1	0	1	1	
С	1	1	0	0	
D	1	1	0	1	
Е	1	1	1	0	
F	1	1	1	1	

- Pin "V" on ATI pin block is First-To-Mate and last-to-break contact, recommended as ground.
 Electrical Rating 50 VDC, 3A.
 Refer to Table 1 for the Tool ID output (Note: Use Pin 'U' of the 19-Pin Connector (Master Side) as Common).



PROJECT #

3rd ANGLE PROJECTION

1031 Goodworth Drive, Apex, NC 27539, USA Tel: +1.919.772.0115 Email: info@ati-ia.com Fax: +1.919.772.8259 www.ati-ia.com ISO 9001 Registered Company

PROPERTY OF ATI INDUSTRIAL AUTOMATION, INC. NOT TO BE REPRODUCED IN ANY MANNER EXCEPT ON ORDER OR WITH PRIOR WRITTEN AUTHORIZATION OF ATI.

DRAWN BY: C. Flesock, 5/17/18 CHECKED BY: B. Smith, 5/17/18

K19P Master and K14 Tool Assembly, Wiring

DRAWING NUMBER SCALE SHEET 3 OF 3 1:1 В 9630-20-K19PM K14T

REVISION

04