



Signal Legend Pin V: 0 VDC (recommended) Pin U: 5-50 VDC 100mA Max (Tool ID)



Rev. -



Note:

- Large views of connectors are 2:1 scale.
 Pin "V" on the amphenol connectors is First-to-mate Last-to-break at the Tool Changer interface. This pin is recommended for use as ground.

Description	Initiator	Date		
See Sheet1	-	-		
T14-T Tool Side (MS3102E22-14S)				

○¢⁄

(

Binary	Output	of	Tool	ID

Binary Output of Tool ID					
Switch					
Selection	Pin	Pin	Pin	Pin	
	Р	S	R	Т	
0	0	0	0	0	
1	0	0	0	1	
2	0	0	1	0	
3	0	0	1	1	
4	0	1	0	0	
5	0	1	0	1	
6	0	1	1	0	
7	0	1	1	1	
8	1	0	0	0	
9	1	0	0	1	

1031 Goodworth Drive, Apex, NC 27539, USA Tel: +1.919.772.0115 Email: info@ati-ia.com Fax: +1.919.772.8259 www.ati-ia.com ISO 9001 Registered Company

PROPERTY OF ATI INDUSTRIAL AUTOMATION, INC. NOT TO BE REPRODUCED IN ANY MANNER EXCEPT ON ORDER OR WITH PRIOR WRITTEN AUTHORIZATION OF ATI.

T19W-M with T14-T Module Drawing

.E	SIZE	DRAWING NUMBER	REVISION
	В	9630-20-T19WM T14T	02